



L'IDROscudo per il tuo scafo

FM41

WARD



AQUA

Technical Features:

- Milky transparency
- Fingerprint proof
- Waxy film
- Prevents galvanic corrosion
- Permanent or removable
- Thixotropic



FM41

DATA SHEET
Released 05.sept.2014
FB 5-21 F03 Rev. 1

Applications:

By evaporation of the solvent, Aquaward leaves a transparent, hard and waxy film, ideally suited as a protective coating, which allows for easy visual inspection of the surface, reading of numbers, labels, etc. Aquaward is intended as a protective shield, in storage and in transit, for boats with lacquered and varnished hulls resistant to solvents and similar, particularly when a colorless, transparent and stain-free film is desired. Aquaward can be used for the protection of finished surfaces, steel and other metals, such as outboard motors, flaps, rudder blades, etc.

How to use:

Aquaward must be applied by spraying with an Airless gun. The ideal temperature for application is 15-20 °C. During storage, the measures to be taken are the same as those applied to other paints and lacquers.

Technical properties:

Colour	Milky transparency
Type of film	Waxy film
Density at 23°C	770 kg/m ³
Viscosity a 23°C (DIN 4 cup)	17 seconds (completely broken thixotropes)
Dry substance	15% of the weight
Flash point	24° C
Aromatic content in solution	< 0,5%
Recommended thickness (wet)	100 µm
Recommended thickness of the layers	10 µm
Drying time	30 min.
Effects in car paint	none
Removability	Hydrocarbon solvents
SST	SST 50 microns, 1000 h
Packs available	5L - 20L - 60L
Storage	24 months

For detailed advice, read the safety data sheet or package label

All data and recommendation are the result of careful tests by our laboratories. They only can be considered as recommendation which correspond to the level of experience of today. The data are given in good faith. However, in view of the multiplicity of possible application and working methods we are not in a position to assume any responsibility or obligations deriving from the use of our products.



Alvida s.r.l.
Via Alessandro Volta 1/B 37026 Pescantina (VR)
Reg. Imp.-C.F.-P.J. IT04650530233 info@alvidasrl.com
Contacts: Filippo Avesani +39 3406740855
Mattia Cipriani +39 3934282612